


- NOTES:
- 1. MATERIAL:
 - COPPER ALLOY, THICKNESS=0.15.
- 2. PLATING:
 - 1.25um(50u")min NI UNDER PLATING.
 - 0.025um(1u")min AU PLATING OVER ALL.
- 3. SPECIFICATION:
 - 3.1 ELECTRICAL CHARACTERISTICS:
 - CURRENT RATING : 10A.
 - VOLTAGE RATING : 50 VAC/DC.
 - LOW LEVEL CONTACT RESISTANCE: 50mΩ MAX
 - 3.2 MECHANICAL CHARACTERISTICS:
 - CONTACT NORMAL FORCE: 50gf min PER PIN AT WORKING STROKE
 - DURABILITY : MATED 10,000 CYCLES AT WORKING STROKE WITHOUT DEGRADING
 - 3.3 ENVIRONMENTAL CHARACTERISTICS:
 - OPERATING TEMPERATURE RANGE : -20°C TO +70°C.
 - 4. TAPE & REEL PACKAGING PER EIA481 STANDARD.
 - 5. DIMENSION SHALL BE INTERPRETED PER ASME Y14.5M-2009.
 - 6. HARMFUL MATERIAL CONTROL FOLLOW "RoHS"



200016-1		2	CARRIER TAPE	P=8mm	WHITE, W=12mm, Q/V, REL=2000 Pcs
1		3.0H 2.3W	ANTIENK CLIPS	1Pcs	NOTES 1,2
ASSEMBLY NUMBER		ITEM	PART NAME	QTY	DESCRIPTION
DIMENSIONS IN MM TOLERANCES UNLESS OTHER SPECIFIED			 HT TR —		
0	= ±—	DWN	APVD	Lansing	
0.0	= ±0.15	CHK	REL	<i>top</i> <i>Esoo</i>	
0.00	= ±0.10	Kent			
ANGLE: 0		NAME			
0.0	= ±3°	CUSTOMER DRAWING FOR 3.0H, 2.3W,			
0.0	= ±1.5°				
REMOVE BURRS. BREAK SHARP EDGES R0.10 MAX		SCALE	DWG		
D0 NOT SCALE PRINT		1:1	A4	NO.	C-200016

MATL			HT TR	—	FIN	—	✓
DVN	Caivanlu	APVD	Lansing	Top-Link Electronics			
CHK	Kent	REL	Top-Link Electronics				
NAME							
CUSTOMER DRAWING FOR 3. OH, 2. 3W, ANTENNA CLIPS							
SCALE	1:1	A4	DWG NO.	C-200016	SHEET	1 OF 1	REV
							A1